

Type	Power	Module Size	Glass size	Weight	Specification				
					Max-Power	Max-Power Voltage	Max-Power Current	Open-Circuit Voltage	Short-circuit Current
Module	W	mm	mm	Kg	W	V	A	V	A
SA280-72	280	1930*980*50	1924*974	19	280	36	7.78	43.2	8.55
SA270-72	270				270	36	7.5	43.2	8.25
SA260-72	260				260	36	7.23	43.2	7.95
SA220-54	220	1450*980*35	1444*974	17	220	27.4	8.03	32.88	8.83
SA210-54	210				210	27.3	7.7	32.76	8.46
SA200-54	200				200	27.22	7.35	32.67	8.08
SA180-72	180	1580*808*35	1574*802	15	180	36.36	4.95	43.64	5.45
SA175-72	175				175	36.15	4.84	43.38	5.33
SA170-72	170				170	36	4.72	43.2	5.19
SA165-72	165				165	36	4.58	43.2	5.04
SA160-72	160				160	36	4.45	43.2	4.88
SA150-36	150	1456*666*35	1450*660	13	150	18	8.34	21.6	9.16
SA140-36	140				140	18	7.78	21.6	8.55
SA130-36/72	130				130	18	7.23	21.6	7.94
SA120-36/72	120				120	18	6.67	21.6	7.34
SA90-36/72	90	1196*534*35	1189*528	8	90	18.72	4.81	22.46	5.28
SA85-36/72	85				85	18	4.72	21.6	5.2
SA80-36/72	80				80	18	4.44	21.6	4.88
SA75-36/72	75				75	18	4.16	21.6	4.58
SA60-36/72	60	810*534*35	804*528	6.5	60	18	3.33	21.6	3.6
SA55-36/72	55				55	18	3.05	21.6	3.36
SA50-36/72	50				50	18	2.78	21.6	3.05
SA40-36	40	610*534*35	605*528	4.5	40	18	2.23	21.6	2.44
SA38-36	38				38	18	2.12	21.6	2.32
SA30-36	30	532*418*28	527*413	3	30	18	1.66	21.6	1.83
SA28-36	28				28	18	1.56	21.6	1.71
SA25-36	25				25	18	1.38	21.6	1.53
SA20-36	20	405*423*28	400*418	2.1	20	18	1.12	21.6	1.24
SA18-36	18				18	18	1	21.6	1.16
SA15-36	15	420*281*28	415*276	1.5	15	18	0.84	21.6	0.92
SA12-36	12	341*280*28	337*276	1.3	12	18	0.67	21.6	0.74
SA10-36	10				10	18	0.56	21.6	0.62
SA8-36	8	285*280*28	280*276	1	8	18	0.45	21.6	0.5
SA6-36	6	204*280*28	200*276	0.8	6	18	0.34	21.6	0.37
SA5-36	5				5	18	0.28	21.6	0.3
SA4-18	4	260*154*18	256*150	0.5	4	9	0.45	10.8	0.48
SA3-18	3	224*146*18	220*142	0.4	3	9	0.23	10.8	0.36
SA2-18	2	150*150*18	146*146	0.3	2	9	0.28	8.4	0.25